

richpos
5000 series

richpos
5000 series



The RichPOS 5015

A POC system that is connected to an external PC box component

Features

- Offers a fanless, clean and silent, smooth operation, heaps of I/O capability
- The PC box has 8 ports that allows for other peripheral connection.
- Allows for a cleaner and spacious counter top since the box PC is installed underneath the counter
- The PC box can be replaced easily for maintenance, the system function will still run and no data will be lost
- To enhance multimedia effect, speakers can be added to the system
- Integrated a customer LCD for interactive or advertising product and service
- Programmable keyboard, omni-directional and in-counter laser scanner, RFID, are all options that can be added according to retailer's preference

The RichPOS 5000 series combines a robust injection die-cast aluminum base with a sleek plexi-glass upper case that incorporates your corporate colors on the inside for that crystal clear scratch-free finish. PC based architecture, it offers a fanless, clean and silent, smooth operation, heaps of I/O capability with standard or customized, color, coordinated add-on peripherals.

Its modular design allows for a variety of screen technologies, sizes and touch panel types. Programmable keyboard, omni-directional and in-counter laser scanner, RFID, customer LCD for interactive or advertising product and service, VFD or LCD pole/line displays, are all options that can be added according to retailer's preference.

For users running POS applications on their PCs and who wish to expedite counter/checkout technology, RichPOS 5000 series is the ideal choice for touch screen LCD displays that lends itself to the reutilization of existing customer's own peripheral devices. The RichPOS 5000 series truly brings a sparkle into your business.



The RichPOS 5515

A back-to-back LCD and system unit equipped

Features

- Has a flexible and lightweight steel frame that is capable of holding a variety of POS accessories.
- Offers a fanless, clean and silent, smooth operation, heaps of I/O capability
- Highly suitable for hypermarket, it provides more counter space and facilitates retailers' transaction process.
- To enhance multimedia effect, speakers can be added to the system.
- Integrated a customer LCD for interactive or advertising product and service
- Programmable keyboard, omni-directional and in-counter laser scanner, RFID, are all options that can be added according to retailer's preference.

FEC

FIRICH ENTERPRISES CO., LTD.
10F, No.75, Sec. 1, Sin Tai Wu Rd., Sijhih City,
Taipei County 221, Taiwan R.O.C.
tel 886-2-2698 1446 fax 886-2-2698 1451


Firich China-Crisom
Room 1508, No. 818, Nansheng (West) Road,
Jing'an District, Shanghai City, China
Post Code: 200041
tel 86-21-51096766 fax 86-21-51096766

Firich Korea Inc.
506 DAERUNGTECHNOTOWN
8th Kasan-dong, 481-11 Gumi-cheon, Seou, Korea
tel 82-42-8376610 fax 82-42-8378070
www.firich.co.kr

Firich USA Inc.
380 Fairview Way, Milpitas, CA 95035, USA
tel 408-942-7043 fax 408-942-7143
sales@firichusa.com
www.firichusa.com

www.firich.com.tw

FEC



richpos
5015

Model	RP-5515
Platform	Pentium 4
Processor	Intel Ultra Low Voltage Celeron-M 1GHz (0K/512K L2 cache) embedded
Memory	256MB ~ 1GB (1 x 200-pin DDR SO-DIMM)
Touch LCD Display	
Size / Resolution	15" TFT LCD (1024 x 768)
Brightness	250 / 350 cd/m ²
Touch Screen	ELO 5-wire Resistive /Fuji 4-wire Resistive
I/O Connectivity	
Serial Port	<ul style="list-style-type: none"> • 3 x External: COM1, COM2 (D-Sub), COM4 (RJ45) • 3 x Internal: COM3 for Primary Touchscreen, COM5 & COM6
Parallel Port	Internal on board
USB port (standard)	<ul style="list-style-type: none"> • 2 x External USB 2.0 • 2 x Internal USB 2.0 (one for Wireless LAN & Other)
Cash Drawer port	1 x 12V RJ11 (single/dual)
Mouse port	N/A
Keyboard port	1 x PS/2 keyboard
LAN port	1 x RJ45 10/100 Base-T
VGA port	Internal on board
Audio port	Line Out and Mic
IDE Hard Disk Drive	Internal 2.5" type 40GB or above
Compact Flash	CF socket onboard
Power Supply	150W External Power Adapter
Construction	Aluminum Die-casting Housing (rear casing), Plexi-Glass Acrylic (front bezel)
Mounting	Wall Mounting Kit (VESA 100 x 100 mm)
Housing Color	Black/Silver
O/S Supported	Win2000, XP Pro (Embedded), WEPOS
EMI/Safety	CE, FCC, UL, RoHS
Operating Temperature	0°C ~ 35°C
Optional Peripherals	
Magnetic Stripe Card Reader	Integrated Triple-Track MCR
MCR 2-in-one	Integrated MCR+Hi-Button / MCR+RFID / MCR+Fingerprint
Barcode Scanner	Laser scanner + 12W Speaker
Customer Pole Display	Integrated VFD type Customer Pole Display
Wireless LAN	Integrated 802.11b/g Wireless LAN Module (USB interface)

All product specifications are subject to change without notice. V0702



richpos
5515

System Box Unit	RP-5015
Platform	Pentium 4
Processor	Intel Ultra Low Voltage Celeron-M 1GHz (0K/512K L2 cache) embedded
Memory	256MB ~ 1GB (1 x 200-pin DDR SO-DIMM)
IDE Hard Disk Drive	2.5" type 40GB or above (removable)
Compact Flash	CF socket onboard
I/O Connectivity	
Serial Port	<ul style="list-style-type: none"> • 5 x External : COM1, COM2, COM 6 (D-Sub), COM4 (RJ45), COM5 (RJ45, Side I/O) • 1 x Internal : COM3 for Primary Touchscreen
Parallel Port	N/A
Standard USB Port	4 x USB 2.0 (2 x internal, 2 x external)
Mouse Port	N/A
Keyboard Port	1 x PS/2 Keyboard
Cash Drawer Port	1 x RJ11 (Single/Dual, 12V)
LAN Port	1 x RJ45 10/100 Base-T
VGA Port	1 x VGA (Side I/O)
Audio Port	1 x Line-out, 1 x Mic-in
LVDS	1 x LVDS connector
DC-Out	1 x 5V/ 12V DC-Out (Side I/O)
Power Supply	100W External Power Adapter
Construction	Aluminum Die-casting Housing
Housing Color	Black
O/S Supported	Win2000, XP (Pro, Embedded), WEPOS
Dimensions (W x H x D)	270 x 65 x 160 mm
Weight	3 kgs
Compliance	CE, FCC, UL, RoHS
Operating Temperature	0°C ~ 35°C

Tower LCD Display Unit	
Size / Resolution	15" (1024 x 768)
Brightness	250 / 350 cd/m ²
Touch Screen	ELO 5-wire Resistive
Power Supply	100W 12V/8.33A Power Adapter (integrated inside of Display Tower)
Speaker	2W speakers (integrated inside of Display Tower)
Construction	Display: Aluminum Die-casting Housing (rear casing), Plexi-Glass Acrylic (front bezel) Tower: Aluminum Die-casting
Housing Color	Black/Silver
Weight	4.5 kgs
Optional Peripherals	
Programmable Keyboard w/MCR	Integrated 32-Key Programmable Keyboard w/Triple-Track MCR
Secondary LCD Display	8.4"/12.1" TFT LCD (Resistive Touch/Non-Touch)
Customer Pole Display	Integrated VFD type Customer Pole Display
Barcode Scanner	Integrated Omnidirectional Laser Barcode Scanner (6082)
Wireless LAN	Integrated 802.11b/g Wireless LAN Module (USB interface)

All product specifications are subject to change without notice. V0702

